



## Datos dimensionales (Pulgadas) Dimensional data (Inches)






A	B	C	D	E	L	M	N
±0.002	±0.002	REF.	MIN.	MAX.	±0.020	±0.005	±0.015
3/8	0.875	0.625	1.062	0.937	1.125	0.250	0.312
1/2	1.000	0.750	1.187	1.062	1.125	0.250	0.312
5/8	1.250	0.937	1.343	1.218	1.188	0.344	0.406
3/4	1.375	1.062	1.468	1.343	1.188	0.344	0.406
7/8	1.500	1.187	1.656	1.531	1.250	0.344	0.406
1	1.625	1.312	1.750	1.625	1.625	0.375	0.438
1-1/8	1.750	1.437	1.870	1.745	1.625	0.375	0.438
1-1/4	1.875	1.562	2.000	1.875	1.625	0.375	0.438
1-3/8	2.000	1.687	2.125	2.000	1.625	0.375	0.438
1-1/2	2.125	1.812	2.250	2.125	1.625	0.375	0.438
1-5/8	2.375	2.000	2.500	2.375	2.125	0.438	0.500
1-3/4	2.500	2.125	2.625	2.500	2.125	0.438	0.500
1-7/8	2.625	2.250	2.750	2.625	2.125	0.438	0.500
2	2.750	2.375	2.937	2.812	2.125	0.438	0.500
2-1/8	3.000	2.500	3.125	3.000	2.125	0.500	0.562
2-1/4	3.125	2.625	3.250	3.125	2.125	0.500	0.562
2-3/8	3.250	2.750	3.375	3.250	2.125	0.500	0.562
2-1/2	3.375	2.875	3.500	3.375	2.125	0.500	0.562
2-5/8	3.375	3.000	3.750	3.625	2.500	0.562	0.625
2-3/4	3.500	3.125	3.875	3.750	2.500	0.562	0.625
2-7/8	3.750	3.250	4.000	3.875	2.500	0.562	0.625
3	3.875	3.375	4.187	4.062	2.500	0.562	0.625

### CONDICIONES DE OPERACIÓN

Velocidad: **Hasta 3,600 RPM**  
 Presion: **125 PSI (8.8Kg/cm<sup>2</sup>)**  
 \*Temperatura: **-57°C ~ 204°C**  
 \*Depende del material del elastómero

### OPERATION CONDITIONS

Speed: **Up to 3,600 RPM**  
 Pressure: **125 PSI (8.8Kg/cm<sup>2</sup>)**  
 \*Temperature: **-57°C ~ 204°C**  
 \*Depends on elastomer material

-  **Partes Metalicas:** Acero Inoxidable 304  
**Metal Parts:** 304 Stainless Steel
-  **Resorte:** Acero inoxidable 304  
**Spring:** 304 Stainless Steel
-  **Cara:** Carbón Grafito, Carburo de Silicio, Carbón Fenólico  
**Rotary Face:** Graphite, Silicon Carbide, Phenolic Carbon
-  **Empaque:** NBR (Nitrilo®), FKM (Vitón®), CR(Neopreno®), EPR (EPDM)  
**Bellow:** NBR (Nitrile®), FKM (Viton®), CR (Neoprene®), EPR (EPDM).
-  **Asiento:** Cerámica, Carburo de Silicio, Carburo de Tungsteno, Acero Inoxidable, Ni-Resist  
**Seat:** Ceramic, Silicon Carbide, Tungsten Carbide, Stainless Steel, Ni-Resist.

