



Datos dimensionales (Milímetros)
Dimensional data (Inches)

A	B	D	E	L	N
±0.05	±0.05	MIN	MAX.	±0.38	±0.38
10	18.1	21.0	20.0	15.0	5.5
11	20.6	24.0	22.0	18.0	5.5
12	20.6	24.0	22.0	18.0	5.5
13	23.1	27.0	25.0	22.0	6.0
14	23.1	27.0	25.0	22.0	6.0
15	26.9	31.0	29.0	23.0	7.0
16	26.9	31.0	29.0	23.0	7.0
17	26.9	31.0	29.0	23.0	7.0
18	30.9	36.0	33.0	24.0	8.0
19	30.9	36.0	33.0	25.0	8.0
20	30.9	36.0	33.0	25.0	8.0
21	35.4	41.0	38.0	25.0	8.0
22	35.4	41.0	38.0	25.0	8.0
23	35.4	41.0	38.0	27.0	8.0
24	35.4	41.0	38.0	27.0	8.0
25	38.2	45.0	40.0	27.0	8.5
28	43.3	50.0	46.0	30.0	9.0
29	43.3	50.0	46.0	30.0	9.0
30	43.3	50.0	46.0	30.0	9.0
32	43.3	50.0	46.0	30.0	9.0
33	53.5	54.0	48.0	39.0	11.5
35	53.5	56.0	50.0	39.0	11.5
38	60.5	62.0	56.0	39.0	11.5
40	60.5	64.0	58.0	39.0	11.5

CONDICIONES DE OPERACIÓN

Velocidad: Hasta 3,600 RPM.
Presion: 115 PSI (8.0Kg/cm²)
Temperatura: -57 °C ~ 204 °C*
**Depende del material del elastómero*

OPERATION CONDITIONS

Speed: Up to 3,600 RPM.
Pressure: 115 PSI (8.0Kg/cm²)
Temperature: -57 °C ~ 204 °C*
**Depends on elastomer material*

● Partes Metalicas: Acero Inoxidable 304
Metal Parts: 304 Stainless Steel

● Resorte: Acero inoxidable 304
Spring: 304 Stainless steel

● Cara: Ceramica, Carburo de Silicio,
Carburo de tungsteno
Rotary Face: Ceramic, Silicon Carbide,
Tungsten Carbide.

● Empaque: NBR (Nitrilo®), FKM (Vitón®),
EPR (EPDM)
● Bellow: NBR (Nitrile®), FKM (Viton®),
EPR (EPDM)

● Asiento: Carbón Grafito, Carburo de Silicio,
Carburo de Tungsteno
● Seat: Graphite, Silicon Carbide,
Tungsten Carbide.

