



Datos dimensionales (Milímetros)
Dimensional data (Mm)

A	B	C	E	L	N
±0.05	±0.05	REF.	MAX.	±0.5	±0.38
6	22.0	8.0	18.0	8.5	4.0
8	22.0	10.0	18.0	11.0	4.0
8	26.0	10.0	24.0	11.0	5.5
9	26.0	11.0	24.0	11.0	5.5
9	26.0	11.0	24.0	11.0	8.0
10	26.0	12.0	24.0	11.0	8.0
11	26.0	13.0	24.0	11.0	8.0
12	26.0	14.0	24.0	13.0	5.5
12A	26.0	14.0	24.0	13.0	8.0
13	26.0	15.0	24.0	13.0	8.0
14	29.5	16.0	32.0	13.0	8.0
15	29.5	17.0	32.0	13.0	8.0
16	29.5	18.0	32.0	13.0	8.0
17	42.0	19.0	39.0	13.0	8.0
18	42.0	20.0	39.0	13.0	8.0
19	42.0	21.0	39.0	13.0	8.0
20	42.0	22.0	39.0	13.0	8.0
20	45.0	22.0	42.0	13.0	10.0
22	45.0	24.0	42.0	13.0	10.0
24	50.0	26.0	47.0	14.0	10.0
25	50.0	27.0	47.0	14.0	10.0
28	57.0	30.0	54.0	15.0	10.0
30	57.0	32.0	54.0	15.0	10.0
32	57.0	34.0	54.0	15.0	10.0
35	63.0	37.0	60.0	16.0	10.0
38	68.0	40.0	65.0	18.0	12.0
40	68.0	42.0	65.0	18.0	12.0
45	73.0	47.0	70.0	20.0	12.0
50	88.0	52.0	85.0	23.0	15.0
55	88.0	57.0	85.0	23.0	15.0
60	110.0	62.0	105.0	30.0	15.0

CONDICIONES DE OPERACIÓN

Velocidad: **Hasta 3,600 RPM.**
Presión: **75 PSI (5.3Kg/cm²)**
Temperatura: **-57 °C ~ 204 °C***
**Depende del material del elastómero*

OPERATION CONDITIONS

Speed: **Up to 3,600 RPM.**
Pressure: **75 PSI (5.3Kg/cm²)**
Temperature: **-57 °C ~ 204 °C***
**Depends on elastomer material*

● **Partes Metalicas:** Acero Inoxidable 304
Metal Parts: 304 Stainless Steel

● **Resorte:** Acero inoxidable 304
Spring: 304 Stainless steel

● **Cara:** Carbón Fenólico, Carbón Grafito,
Carburo de Silicio
Rotary Face: Phenolic Carbon, Graphite,
Silicon Carbide.

● **Empaque:** EPR (EPDM), NBR (Nitrilo®), FKM (Vitón®)
Bellow: EPR (EPDM), NBR (Nitrile®), FKM (Viton®)

● **Asiento:** Cerámica, Carburo de Silicio
Seat: Ceramic, Silicon Carbide

