



Datos dimensionales (Pulgadas)

Dimensional data (Inches)

A	B	E	E ₁	D	L	L ₁	L ₂	M	N
±0.002	±0.002	±0.002	±0.002	REF.	±0.015	±0.005	±0.005	±0.005	±0.015
1/2	1.000	1.130	-	1.320	0.188	0.345	-	0.250	0.312
5/8	1.187	1.440	-	1.625	0.265	0.345	-	0.282	0.344
5/8	1.250	1.440	-	1.625	0.265	0.345	-	0.344	0.406
3/4	1.375	1.575	-	1.719	0.235	0.375	-	0.344	0.406
3/4	1.375	1.575	-	1.719	0.235	0.375	-	0.167	0.200
3/4	1.375	-	1.771	1.719	0.235	-	0.452	0.167	0.200
1	1.625	1.850	-	2.008	0.312	0.393	-	0.375	0.437
1-1/8	1.889	2.047	-	2.244	0.314	0.432	-	0.252	0.314

CONDICIONES DE OPERACIÓN

Velocidad: Hasta 5,000 RPM.

Presión: 100 PSI (7.0Kg/cm²)

Temperatura: -57°C ~ 204°C*

*Depende del material del elastómero

OPERATION CONDITIONS

Speed: Up to 5,000 RPM.

Pressure: 100 PSI (7.0Kg/cm²)

Temperature: -57°C ~ 204°C*

*Depends on elastomer material

● **Partes Metálicas:** Acero Inoxidable 304 / Latón
Metal Parts: 304 Stainless Steel, Brass

● **Resorte:** Acero inoxidable 304
Spring: 304 Stainless Steel

● **Cara:** Carbón Fenólico, Carbón Grafito,
Carburo de Silicio
Rotary Face: Phenolic Carbon, Graphite,
Silicon Carbide

● **Empaque:** NBR (Nitrilo®), FKM (Vitón®),
EPR. (EPDM)
Bellow: NBR (Nitrilo®), FKM (Vitón®),
EPR (EPDM)

● **Asiento:** Cerámica, Carburo de Silicio
Seat: Ceramic, Silicon Carbide

