



Datos dimensionales Dimensional data (Mm)

Componentes (Pulgadas)			Components (Inches)		
A	E	D	L	L ₁	L ₃
±0.002	±0.002	±0.010	±0.015	±0.005	±0.015
1/2	1.130	1.320	0.188	0.345	0.210
1/2	1.185	1.385	0.188	0.345	0.210
1/2	1.315	1.503	0.188	0.345	0.210
5/8	1.440	1.625	0.265	0.345	0.200
5/8	1.504	1.718	0.265	0.345	0.200
5/8	1.540	1.740	0.265	0.345	0.200

Integrados (Pulgadas)

Integrados (Pulgadas)			Integrated (Inches)		
A	E	D	L	L ₁	L ₃
±0.002	±0.002	±0.010	±0.015	±0.005	±0.015
1/2	1.130	1.320	0.188	0.345	0.405
1/2	1.185	1.385	0.188	0.345	0.405
1/2	1.315	1.503	0.144	0.345	0.361
5/8	1.440	1.625	0.265	0.345	0.485
5/8	1.504	1.818	0.265	0.345	0.485
5/8	1.554	1.740	0.265	0.345	0.485

Integrados (Milímetros)

Integrados (Milímetros)			Integrated (Mm)		
A	E	D	L	L ₁	L ₃
±0.05	±0.05	±0.25	±0.38	±0.13	±0.38
12	28.70	33.53	5.08	8.76	10.11
12	30.10	35.18	5.08	8.76	10.11

CONDICIONES DE OPERACIÓN

Velocidad: **Hasta 10,000 RPM.**
 Presion: **100 PSI (8.8Kg/cm²)**
 Temperatura: **-57 °C ~ 204 °C***

**Depende del material del elastómero*

OPERATION CONDITIONS

Speed: **Up to 10,000 RPM.**
 Pressure: **100 PSI (8.8Kg/cm²)**
 Temperature: **-57 °C ~ 204 °C***

**Depends on elastomer material*

- **Partes Metalicas:** Acero Inoxidable 304 / Latón
Metal Parts: 304 Stainless Steel, Brass
- **Resorte:** Acero inoxidable 304
Spring: 304 Stainless Steel
- **Cara:** Carbón Fenolico, Carbón Grafito,
Carburo de Silicio
Rotary Face: Phenolic Carbon, Graphite,
Silicon Carbide
- **Empaque:** NBR (Nitrilo®), FKM (Vitón®),
EPR. (EPDM)
- **Bellow:** NBR (Nitrile®), FKM (Vitón®),
EPR (EPDM)
- **Asiento:** Acero Sinterizado, Cerámica, Carburo de Silicio
Seat: Sintered Steel, Ceramic, Silicon Carbide

