



CONDICIONES DE OPERACIÓN

Velocidad: Hasta 3,600 RPM
 Presion: 170 PSI (12Kg/cm²)
 *Temperatura: -57°C ~ 204°C
 *Depende del material del elastómero

OPERATION CONDITIONS

Speed: Up to 3,600 RPM
 Pressure: 170 PSI (12Kg/cm²)
 *Temperature: -57°C ~ 204°C
 *Depends on elastomer material

- **Partes Metalicas:** Acero Inoxidable 304
Metal Parts: 304 Stainless Steel
- **Resorte:** Acero inoxidable 304
Spring: 304 Stainless Steel
- **Cara:** Carbón Grafito, Carburo de Silicio
Rotary Face: Graphite, Silicon Carbide
- **Empaque:** NBR (Nitrilo®), FKM (Vitón®) EPR (EPDM)
Bellow: NBR (Nitrile), FKM (Viton®), EPR (EPDM)
- **Asiento:** Cerámica, Carburo de Silicio
Seat: Ceramic, Silicon Carbide

Se ofrece como estándar con estacionaria tipo G60
 Offered as standard with stationary type G60

Datos dimensionales (Milímetros) Dimensional data (Millimeters)

A	B	C	D	E	L	M	N
±0.05	±0.05	REF.	MIN.	MAX.	±0.05	±0.05	±0.012
10	21.0	17.0	24.0	22.5	25.9	5.5	6.6
12	23.0	19.0	26.0	25.0	25.9	5.5	6.6
14	25.0	21.0	30.0	28.5	28.4	5.5	6.6
15	27.0	23.0	30.0	28.5	28.4	5.5	6.6
16	27.0	23.0	30.0	28.5	28.4	5.5	6.6
18	33.0	27.0	33.0	32.0	30.0	7.0	7.5
19	35.0	29.0	38.0	37.0	30.0	7.0	7.5
20	35.0	29.0	38.0	37.0	30.0	7.0	7.5
22	37.0	31.0	38.0	37.0	30.0	7.0	7.5
24	39.0	33.0	44.0	42.5	32.5	7.0	7.5
25	40.0	34.0	44.0	42.5	32.5	7.0	7.5
28	43.0	37.0	50.0	49.0	35.0	7.0	7.5
30	45.0	39.0	50.0	49.0	35.0	7.0	7.5
32	48.0	42.0	55.0	53.5	35.0	7.0	7.5
33	48.0	42.0	55.0	53.5	35.0	7.0	7.5
35	50.0	44.0	59.0	57.0	35.0	7.0	7.5
38	56.0	49.0	61.0	59.0	36.0	8.0	9.0
40	58.0	51.0	64.0	62.0	36.0	8.0	9.0
42	61.0	54.0	67.0	65.5	36.0	8.0	9.0
43	61.0	54.0	67.0	65.5	36.0	8.0	9.0
45	63.0	56.0	70.0	68.0	36.0	8.0	9.0
48	66.0	59.0	74.0	70.5	36.0	8.0	9.0
50	70.0	62.0	77.0	74.0	38.0	8.5	9.5
53	73.0	65.0	81.0	78.5	36.5	8.5	11.0
55	75.0	67.0	83.0	81.0	36.5	8.5	11.0
58	78.0	70.0	88.0	85.5	41.5	8.5	11.0
60	80.0	72.0	91.0	88.5	41.5	8.5	11.0
65	85.0	77.0	96.0	93.5	41.5	8.5	11.0
68	90.0	81.0	100.0	96.5	41.2	9.5	11.3
70	92.0	83.0	103.0	99.5	48.7	9.5	11.3
75	97.0	88.0	110.0	107.0	48.7	9.5	11.3
80	105.0	95.0	116.0	112.0	48.0	10.0	12.0
85	110.0	100.0	124.0	120.0	46.0	10.0	14.0
90	115.0	105.0	131.0	127.0	51.0	10.0	14.0
95	120.0	110.0	136.0	132.0	51.0	10.0	14.0
100	125.0	115.0	140.0	137.0	51.0	10.0	14.0

