

TS15A



Datos dimensionales (Pulgadas)				
Dimensional data (Inches)				
MEDIDA SIZE No.	A ±0.002	D MIN	E ±0.015	L ±0.015
16	1.000	1.750	1.500	1.500
18	1.125	1.875	1.625	1.562
20	1.250	2.000	1.750	1.688
22	1.375	2.125	1.875	1.750
24	1.500	2.312	2.062	1.750
26	1.625	2.500	2.250	1.750
28	1.750	2.625	2.375	1.750
30	1.875	2.750	2.500	1.875
32	2.000	2.937	2.687	1.938
34	2.125	3.125	2.875	2.063
36	2.250	3.250	3.000	2.063
38	2.375	3.375	3.125	2.250
40	2.500	3.500	3.250	2.250
42	2.625	3.750	3.437	2.313
44	2.750	3.875	3.562	2.313
46	2.875	4.000	3.687	2.563
48	3.000	4.188	3.875	2.750
50	3.125	4.437	4.062	2.750
52	3.250	4.562	4.187	2.750
54	3.375	4.687	4.312	2.750
56	3.500	4.812	4.437	2.750
58	3.625	4.937	4.562	3.000
60	3.750	5.062	4.687	3.250
62	3.875	5.187	4.812	3.500
64	4.000	5.312	4.937	3.625

CONDICIONES DE OPERACIÓN

Velocidad: **Hasta 3,600 RPM**
 Presion: **150 PSI (10.6Kg/cm²)**
 *Temperatura: **-57°C ~ 316°C**
 *Depende del material del elastómero

OPERATION CONDITIONS

Speed: **Up to 3,600 RPM**
 Pressure: **150 PSI (10.6Kg/cm²)**
 *Temperature: **-57°C ~ 316°C**
 *Depends on elastomer material

- **Partes Metalicas:** Acero inoxidable 316
Metal Parts: 316 Stainless Steel
- **Resorte:** Acero inoxidable 316
Spring: 316 Stainless Steel
- **Cara:** Carbón Grafito, Carburo de Silicio, Carburo de Tungsteno
Rotary Face: Graphite, Silicon Carbide, Tungsten Carbide
- **Empaque:** NBR (Nitrilo®), FKM (Vitón®), CR (Neopreno®), E.P.R (EPDM), Kalrez (FFKM), Aflas (TFE/P), Creavey (PTFE/FKM) y Silicón (VMQ)
- **Bellow:** NBR (Nitrile), FKM (Viton®), CR (Neopreno®), E.P.R (EPDM), Kalrez (FFKM), Aflas (TFE/P), Creavey (PTFE/FKM) y Silicón (VMQ)
- **Asiento:** Cerámica, Carburo de Silicio, Carburo de Tungsteno, Acero Inoxidable, Ni-Resist.
Seat: Ceramic, Silicon Carbide, Tungsten Carbide, Stainless Steel, Ni- Resist.

