



Datos dimensionales (Pulgadas)

Dimensional data (Inches)

A	B	C	D	E	L ₁	L ₂	K	M	N
±0.002	±0.002	REF.	MIN.	MAX.	±0.020	±0.020	±0.005	±0.005	±0.015
5/8	1.250	0.937	1.343	1.218	1.312	0.875	0.312	0.344	0.406
3/4	1.375	1.062	1.468	1.343	1.312	0.875	0.375	0.344	0.406
7/8	1.500	1.187	1.656	1.531	1.375	0.937	0.375	0.344	0.406
1	1.625	1.312	1.750	1.625	1.562	1.000	0.375	0.375	0.438
1-1/8	1.750	1.437	1.870	1.745	1.625	1.062	0.375	0.375	0.438
1-1/4	1.875	1.562	2.000	1.875	1.625	1.062	0.375	0.375	0.438
1-3/8	2.000	1.687	2.125	2.000	1.687	1.125	0.375	0.375	0.438
1-1/2	2.125	1.812	2.250	2.125	1.687	1.125	0.375	0.375	0.438
1-5/8	2.375	2.000	2.500	2.375	2.000	1.375	0.375	0.438	0.500
1-3/4	2.500	2.125	2.625	2.500	2.000	1.375	0.375	0.438	0.500
1-7/8	2.625	2.250	2.750	2.625	2.125	1.500	0.375	0.438	0.500
2	2.750	2.375	2.937	2.812	2.125	1.500	0.375	0.438	0.500
2-1/8	3.000	2.500	3.125	3.000	2.375	1.687	0.500	0.500	0.562
2-1/4	3.125	2.625	3.250	3.125	2.375	1.687	0.500	0.500	0.562
2-3/8	3.250	2.750	3.375	3.250	2.500	1.812	0.500	0.500	0.562
2-1/2	3.375	2.875	3.500	3.375	2.500	1.812	0.500	0.500	0.562
2-5/8	3.375	3.000	3.750	3.625	2.750	1.937	0.500	0.562	0.625
2-3/4	3.500	3.125	3.875	3.750	2.750	1.937	0.500	0.562	0.625
2-7/8	3.750	3.250	4.000	3.875	2.875	2.062	0.500	0.562	0.625
3	3.875	3.375	4.187	4.062	2.875	2.062	0.500	0.562	0.625

Dimensiones dentro de la Norma ASTM (Excepto Columna "C").

La Columna "C" depende del fabricante de la bomba.

Dimensions inside Norma ASTM (except "C" column).

The "c" column depends on the manufacturer of the pump.

CONDICIONES DE OPERACIÓN

Velocidad: Hasta 3,600 RPM

Presion: 150 PSI (10.5Kg/cm²)

*Temperatura: -57°C ~ 204°C

*Depende del material del elastómero

OPERATION CONDITIONS

Speed: Up to 3,600 RPM

Pressure: 150 PSI (10.5Kg/cm²)

*Temperature: -57°C ~ 204°C

*Depends on elastomer material

 **Partes Metalicas:** Acero Inoxidable 316, 304
Metal Parts: 316, 304 Stainless Steel

 **Resorte:** Acero inoxidable 316, 304
Spring: 316, 304 Stainless Steel

Cara: Carburo de Tungsteno, Carburo de Silicio,
Carbón Grafito
 **Rotary Face:** Tungsten Carbide, Silicon Carbide,
Graphite

 **Empaque:** NBR (Nitrilo®), EPR (EPDM)
Bellow: NBR (Nitrile®), EPR (EPDM)

 **Asiento:** Carburo de Silicio, Carburo de Tungsteno
Seats: Silicon Carbide, Tungsten Carbide

