



CONDICIONES DE OPERACIÓN

Velocidad: Hasta 3,600 R.P.M.
 Presion: 325 PSI (22.8Kg/cm²)
 *Temperatura: -57°C ~ 316°C
 *Depende del material del elastómero

OPERATION CONDITIONS

Velocity: Up to 3,600 R.P.M.
 Pressure: 325 PSI (22.8Kg/cm²)
 *Temperature: -57°C ~ 316°C
 *Depends on elastomer material

-  Partes Metalicas: Acero inoxidable 316
 Metal Parts: 316 Stainless Steel
-  Resorte: Hastelloy "C"
 Spring: Hastelloy "C"
-  Cara: Carbón Grafito, PTFE/Fibra de Vidrio
 Rotary Face: Graphite, PTFE/Fiberglass

-  **Empaque:** NBR (Nitrilo®), FKM (Vitón®), CR (Neopreno®), E.P.R (EPDM), Kalrez/Perlast (FFKM), Aflas (TFE/P), Creavey (PTFE/FKM) y Silicón (VMQ)
-  **Bellow:** NBR (Nitrile), FKM (Viton®), CR (Neopreno®), E.P.R (EPDM), Kalrez/Perlast (FFKM), Aflas (TFE/P), Creavey (PTFE/FKM) y Silicón (VMQ)
-  **Asiento:** Cerámica, Carburo de Silicio, Carburo de Tungsteno, Acero Inoxidable, Ni-Resist.
Seat: Ceramic, Silicon Carbide, Tungsten Carbide, Stainless Steel, Ni- Resist.

Datos dimensionales (Pulgadas)

Dimensional data (Inches)

MEDIDA SIZE No.	A ±0.002	D MIN	E ±0.015	L ±0.015
8	0.500	1.156	1.031	0.812
10	0.625	1.312	1.187	0.750
12	0.750	1.437	1.312	0.875
14	0.875	1.562	1.437	0.937
15	0.937	1.750	1.562	1.000
16	1.000	1.750	1.562	1.000
18	1.125	1.875	1.687	1.062
20	1.250	2.000	1.875	1.062
22	1.375	2.125	2.000	1.125
24	1.500	2.250	2.125	1.125
26	1.625	2.500	2.375	1.375
28	1.750	2.625	2.500	1.375
30	1.875	2.750	2.625	1.375
32	2.000	2.875	2.750	1.375
34	2.125	3.125	3.000	1.687
36	2.250	3.250	3.125	1.687
38	2.375	3.375	3.250	1.687
40	2.500	3.500	3.375	1.687
42	2.625	3.625	3.500	1.687
44	2.750	3.750	3.625	1.687
46	2.875	3.875	3.750	1.687
48	3.000	4.000	3.812	1.687
50	3.125	4.062	3.937	1.687
52	3.250	4.250	4.125	1.687
54	3.375	4.375	4.250	1.687
56	3.500	4.500	4.375	1.687
58	3.625	4.625	4.500	1.687
60	3.750	4.750	4.625	1.687
62	3.875	4.875	4.750	1.687
64	4.000	5.000	4.875	1.687

