



| Datos dimensionales (Pulgadas) |        |         |        |        |        |
|--------------------------------|--------|---------|--------|--------|--------|
| Dimensional data (Inches)      |        |         |        |        |        |
| MEDIDA<br>SIZE<br>No.          | A      | Escalón | D      | E      | L      |
|                                | ±0.002 | ±0.002  | ±0.002 | ±0.015 | ±0.015 |
| 16                             | 1.000  | 0.875   | 1.625  | 1.437  | 1.312  |
| 18                             | 1.125  | 1.000   | 1.750  | 1.562  | 1.375  |
| 20                             | 1.250  | 1.125   | 1.875  | 1.687  | 1.375  |
| 22                             | 1.375  | 1.125   | 2.125  | 1.937  | 1.687  |
| 24                             | 1.500  | 1.250   | 2.125  | 1.937  | 1.437  |
| 26                             | 1.625  | 1.375   | 2.437  | 2.250  | 1.593  |
| 28                             | 1.750  | 1.500   | 2.500  | 2.312  | 1.750  |
| 30                             | 1.875  | 1.625   | 2.687  | 2.500  | 1.750  |
| 32                             | 2.000  | 1.750   | 2.812  | 2.625  | 1.750  |
| 34                             | 2.125  | 1.875   | 3.000  | 2.812  | 2.062  |
| 36                             | 2.250  | 2.000   | 3.031  | 2.843  | 1.750  |
| 38                             | 2.375  | 2.125   | 3.187  | 3.000  | 2.062  |
| 40                             | 2.500  | 2.250   | 3.312  | 3.125  | 1.750  |
| 42                             | 2.625  | 2.375   | 3.437  | 3.250  | 2.062  |
| 44                             | 2.750  | 2.500   | 3.562  | 3.375  | 2.062  |
| 46                             | 2.875  | 2.625   | 3.687  | 3.500  | 2.062  |
| 48                             | 3.000  | 2.750   | 3.812  | 3.625  | 2.062  |
| 50                             | 3.125  | 2.875   | 3.937  | 3.750  | 2.062  |
| 52                             | 3.250  | 3.000   | 4.062  | 3.875  | 2.062  |
| 54                             | 3.375  | 3.125   | 4.187  | 4.000  | 2.062  |
| 56                             | 3.500  | 3.250   | 4.312  | 4.125  | 2.062  |
| 58                             | 3.625  | 3.375   | 4.437  | 4.250  | 2.062  |
| 60                             | 3.750  | 3.500   | 4.562  | 4.375  | 2.062  |
| 62                             | 3.875  | 3.625   | 4.687  | 4.500  | 2.062  |
| 64                             | 4.000  | 3.750   | 4.812  | 4.625  | 2.062  |

### CONDICIONES DE OPERACIÓN

Velocidad: Hasta 3,600 R.P.M.  
 Presion: 300 PSI (21Kg/cm<sup>2</sup>)  
 \*Temperatura: -57°C ~ 316°C  
 \*Depende del material del elastómero

### OPERATION CONDITIONS

Velocity: Up to 3,600 R.P.M.  
 Pressure: 300 PSI (21Kg/cm<sup>2</sup>)  
 \*Temperature: -57°C ~ 316°C  
 \*Depends on elastomer material

- Partes Metalicas: Acero inoxidable 316  
 Metal Parts: 316 Stainless Steel
- Resorte: Hastelloy "C"  
 Spring: Hastelloy "C"
- Cara: Carbón Grafito  
 Rotary Face: Graphite
- Empaque: NBR (Nitrilo®), FKM (Vitón®), CR (Neopreno®), E.P.R (EPDM), Kalrez/Perlast (FFKM), Aflas (TFE/P), Creavey (PTFE/FKM) y Silicón (VMQ)
- Bellow: NBR (Nitrile), FKM (Viton®), CR (Neopreno®), E.P.R (EPDM), Kalrez/Perlast (FFKM), Aflas (TFE/P), Creavey (PTFE/FKM) y Silicón (VMQ)
- Asiento: Cerámica, Carburo de Silicio, Carburo de Tungsteno, Acero Inoxidable, Ni-Resist.  
 Seat: Ceramic, Silicon Carbide, Tungsten Carbide, Stainless Steel, Ni- Resist.

