



CONDICIONES DE OPERACIÓN

Velocidad: **Hasta 3,600 RPM**
 Presion: **200 PSI (14Kg/cm²)**
 *Temperatura: **-57°C ~ 316°C**
 *Depende del material del elastómero

OPERATION CONDITIONS

Speed: **Up to 3,600 RPM**
 Pressure: **200 PSI (14Kg/cm²)**
 *Temperature: **-57°C ~ 316°C**
 *Depends on elastomer material

- **Partes Metalicas:** Acero inoxidable 316
Metal Parts: 316 Stainless Steel
- **Resorte:** Hastelloy "C"
Spring: Hastelloy "C"
- **Cara:** Carbón Grafito, PTFE/Fibra de Vidrio
Rotary Face: Graphite, PTFE/Fiberglass
- **Empaque:** NBR (Nitrilo®), FKM (Vitón®), CR (Neopreno®), E.P.R (EPDM), Kalrez (FFKM), Aflas (TFE/P), Creavey (PTFE/FKM) y Silicón (VMQ)
- **Bellow:** NBR (Nitrile), FKM (Viton®), CR (Neopreno®), E.P.R (EPDM), Kalrez (FFKM), Aflas (TFE/P), Creavey (PTFE/FKM) y Silicón (VMQ)
- **Asiento:** Cerámica, Carburo de Silicio, Carburo de Tungsteno, Acero Inoxidable, Ni-Resist.
Seat: Ceramic, Silicon Carbide, Tungsten Carbide, Stainless Steel, Ni- Resist.

Datos dimensionales (Pulgadas)

Dimensional data (Inches)

MEDIDA SIZE No.	A ±0.002	D MIN	E ±0.015	L ±0.015
8	0.500	1.062	0.937	0.937
10	0.625	1.187	1.062	0.937
12	0.750	1.312	1.187	0.937
14	0.875	1.437	1.312	0.937
15	0.937	1.562	1.437	1.000
16	1.000	1.562	1.437	1.000
18	1.125	1.687	1.562	1.000
20	1.250	1.812	1.687	1.000
22	1.375	2.062	1.937	1.375
24	1.500	2.062	1.937	1.125
26	1.625	2.375	2.250	1.156
28	1.750	2.437	2.312	1.375
30	1.875	2.625	2.500	1.375
32	2.000	2.750	2.625	1.375
34	2.125	2.937	2.812	1.687
36	2.250	2.968	2.843	1.375
38	2.375	3.125	3.000	1.687
40	2.500	3.250	3.125	1.375
42	2.625	3.375	3.250	1.687
44	2.750	3.500	3.375	1.687
46	2.875	3.625	3.500	1.687
48	3.000	3.750	3.625	1.687
50	3.125	3.875	3.750	1.687
52	3.250	4.000	3.875	1.687
54	3.375	4.125	4.000	1.687
56	3.500	4.250	4.125	1.687
58	3.625	4.375	4.250	1.687
60	3.750	4.500	4.375	1.687
62	3.875	4.625	4.500	1.687
64	4.000	4.750	4.625	1.687

