



Utilizado en bombas Flygt numero /  
Used for Flygt pump no:

2060/3041 - 171/3041 - 180/3041 -  
281/3057/3060/3066/3067 - 890/3067 -  
690/3067 - 590/3067 - 250/3067 - 170/3067 -  
090/3067 - 180/3068/3085 - 091/3085 -  
092/3085 - 120/3085 - 170/3085 - 171/3085 -  
172/3085 - 180/3085 - 181/3085 - 182/3085 -  
890/3085 - 891

## CONDICIONES DE OPERACIÓN

Velocidad: **Hasta 2,800 RPM**  
Presion: **94.27PSI (6.63Kg/cm<sup>2</sup>)**  
Temperatura: **-15°C ~ 204°C**

## OPERATION CONDITIONS

Speed: **Up to 2,800 RPM**  
Pressure: **94.27PSI (6.63Kg/cm<sup>2</sup>)**  
Temperature: **-15°C ~ 204°C**

-  **Partes Metalicas:** Acero inoxidable 304  
**Metal Parts:** 304 Stainless Steel
-  **Resorte:** Acero inoxidable 304  
**Spring:** 304 Stainless Steel
-  **Cara:** Carburo de Tungsteno  
**Rotary Face:** Tungsten Carbide
-  **Empaque:** FKM (Viton®)  
**Bellow:** FKM (Viton®)
-  **Asiento:** Carburo de Tungsteno  
**Seat:** Tungsten Carbide
-  **Empaque Asiento:** FKM (Viton)  
**Seat Bellow:** FKM (Viton)

