



Datos dimensionales (Milímetros) Dimensional data (Millimeters)

Medidas Sizes	d	D	D ₁	L ₁	L ₂	M
12	12	22	23	8	42	10

CONDICIONES DE OPERACIÓN

Velocidad: Hasta 3,600 R.P.M.

Presion: 145 PSI (10Kg/cm²)

*Temperatura: -37°C ~ 204°C

**Depende del material del elastómero*

OPERATION CONDITIONS

Velocity: Up to 3,600 R.P.M.

Pressure: 145 PSI (10Kg/cm²)

*Temperature: -37°C ~ 204°C

**Depends on elastomer material*

● Partes Metalicas: Acero inoxidable 304, 316
Metal Parts: 304, 316 Stainless Steel

● Resorte: Acero inoxidable 304, 316
Spring: 304, 316 Stainless Steel

● Cara: Carburo de Silicio, Carburo de Tungsteno
Rotary Face: Silicon Carbide, Tungsten Carbide

● Empaque: NBR (Nitrilo®), FKM (Vitón®)
Bellow: NBR (Nitrile), FKM (Viton®)

● Asiento: Carbón Grafito, Carburo de Silicio, Carburo de Tungsteno
Seat: Graphite, Silicon Carbide, Tungsten Carbide

