



Datos dimensionales (Milímetros)

Dimensional data (Millimeters)

Medidas Sizes	d	D	D ₁	L ₁	L ₂
12	12	29	23	8	43
16	16	35	27	11.5	52.5

CONDICIONES DE OPERACIÓN

Velocidad: Hasta 3,600 R.P.M.

Presión: 145 PSI (10Kg/cm²)

*Temperatura: -37 °C ~ 204 °C

*Depende del material del elastómero

OPERATION CONDITIONS

Velocity: Up to 3,600 R.P.M.

Pressure: 145 PSI (10Kg/cm²)

*Temperature: -37 °C ~ 204 °C

* Depends on elastomer material

● Partes Metálicas: Acero inoxidable 304, 316
Metal Parts: 304, 316 Stainless Steel

● Resorte: Acero inoxidable 304, 316
Spring: 304, 316 Stainless Steel

● Cara: Carburo de Silicio, Carburo de Tungsteno
Rotary Face: Silicon Carbide, Tungsten Carbide

● Empaque: NBR (Nitrilo®), FKM (Vitón®)
Bellows: NBR (Nitrile), FKM (Viton®)

● Asiento: Carbón Grafito, Carburo de Silicio, Carburo de Tungsteno
Seat: Graphite, Silicon Carbide, Tungsten Carbide

