

Datos dimensionales (Milímetros)

Dimensional data (Millimeters)

Medidas Sizes	d	D	D ₁	L ₁	L ₂
12	12	46	23.7	8	15.5
16	16	46	27.7	8	15.5

CONDICIONES DE OPERACIÓN

Velocidad: Hasta 3,600 R.P.M.

Presion: 145 PSI (10Kg/cm²)

*Temperatura: -37°C ~ 204°C

**Depende del material del elastómero*






OPERATION CONDITIONS

Velocity: Up to 3,600 R.P.M.

Pressure: 145 PSI (10Kg/cm²)

*Temperature: -37°C ~ 204°C

** Depends on elastomer material*

-  **Partes Metalicas:** Acero inoxidable 304, 316
Metal Parts: 304, 316 Stainless Steel
-  **Resorte:** Acero inoxidable 304, 316
Spring: 304, 316 Stainless Steel
-  **Cara:** Carburo de Silicio, Carburo de Tungsteno
Rotary Face: Silicon Carbide, Tungsten Carbide
-  **Empaque:** NBR (Nitrilo®), FKM (Vitón®)
Bellow: NBR (Nitrile), FKM (Viton®)
-  **Asiento:** Carbón Grafito, Carburo de Silicio, Carburo de Tungsteno
Seat: Graphite, Silicon Carbide, Tungsten Carbide

