



Datos dimensionales (Pulgadas)

Dimensional data (Inches)

MEDIDA SIZE No.	A	B	D	E	L
16	±0.002	±0.002	±0.002	±0.015	±0.015
20	1.000	2.125	2.562	2.149	1.768
24	1.250	2.363	2.702	2.355	2.395
24	1.500	2.875	3.250	3.000	2.340
24	1.500	2.875	3.453	3.000	2.481

CONDICIONES DE OPERACIÓN

Velocidad: Hasta 3,600 R.P.M.
 Presion: 250 PSI (17.6Kg/cm²)
 *Temperatura: -15°C ~ 204°C
 *Depende del material del elastómero

OPERATION CONDITIONS

Velocity: Up to 3,600 R.P.M.
 Pressure: 250 PSI (17.6Kg/cm²)
 *Temperature: -15°C ~ 204°C
 *Depends on elastomer material

-  **Partes Metalicas:** Acero inoxidable 304, 316
Metal Parts: 304, 316 Stainless Steel
-  **Resorte:** Acero inoxidable 304, 316
Spring: 304, 316 Stainless Steel
-  **Cara:** Carburo de Silicio.
Rotary Face: Silicon Carbide.
-  **Empaque:** FKM (Vitón®)
Bellow: FKM (Vitón®)
-  **Asiento:** Carburo de Silicio.
Seat: Silicon Carbide.

