



CONDICIONES DE OPERACIÓN

Velocidad: **Hasta 3,600 RPM**
 Presion: **300 PSI (21.1 Kg/cm²)**
 *Temperatura: **-57°C ~ 316°C**
 *Depende del material del elastómero

OPERATION CONDITIONS

Speed: **Up to 3,600 RPM**
 Pressure: **300 PSI (21.1 Kg/cm²)**
 *Temperature: **-57°C ~ 316°C**
 *Depends on elastomer material

Datos dimensionales (Pulgadas) Dimensional data (Inches)

MEDIDA SIZE No.	A ±0.002	D MIN	E ±0.015	L ±0.015
16	1.000	1.582	1.457	1.250
18	1.125	1.812	1.687	1.250
20	1.250	1.937	1.812	1.312
22	1.375	2.062	1.937	1.437
24	1.500	2.187	2.062	1.437
26	1.625	2.312	2.187	1.437
28	1.750	2.437	2.312	1.437
30	1.875	2.562	2.437	1.500
32	2.000	2.687	2.562	1.500
34	2.125	2.812	2.687	1.500
36	2.250	2.937	2.812	1.562
38	2.375	3.062	2.937	1.562
40	2.500	3.312	3.187	1.562
42	2.625	3.437	3.312	1.625
44	2.750	3.562	3.437	1.625
46	2.875	3.750	3.625	1.687
48	3.000	3.875	3.750	1.687
50	3.125	4.000	3.875	1.750
52	3.250	4.125	4.000	1.750
54	3.375	4.250	4.125	1.750
56	3.500	4.375	4.250	1.875
58	3.625	4.500	4.375	1.875
60	3.750	4.625	4.500	1.875
62	3.875	4.750	4.625	1.875
64	4.000	4.875	4.750	1.875

Partes Metalicas: Acero inoxidable 316, Hastelloy "C".
 Metal Parts: 316 Stainless Steel, Hastelloy "C".

Resorte: Hastelloy "C", Aleación AM-350
 Spring: Hastelloy "C", Alloy AM-350

Cara: Carbón Grafito, Carburo de Tungsteno, Carburo de Silicio.
 Rotary Face: Graphite, Tungsten Carbide, Silicon Carbide.

Empaque: NBR (Nitrilo®), FKM (Vitón®), E.P.R (EPDM), Kalrez/Perlast (FFKM), Aflas (TFE/P), Creavey (PTFE/FKM).
 Bellow: NBR (Nitrile), FKM (Viton®), E.P.R (EPDM), Kalrez/Perlast (FFKM), Aflas (TFE/P), Creavey (PTFE/FKM).

Asiento: Cerámica, Carburo de Silicio, Carburo de Tungsteno.
 Seat: Ceramic, Silicon Carbide, Tungsten Carbide.

